



SafetyGear

PRODUCT CATALOGUE 2026

Industrial safety equipment

PPE · Fire fighting & fire protection · Gas detection · Emergency & rescue · Site safety

SECTION

Personal Protective Equipment

Head-to-toe protection specified to EN and ANSI/ISEA standards for industrial, construction and energy sites.

HEAD PROTECTION

SKU	Product	Standards
PPE-HD-101	Full-Brim Safety Helmet Full-brim HDPE helmet with 4-point textile suspension and ratchet adjustment — shades face and neck on outdoor sites.	EN 397; ANSI/ISEA Z89.1 Type I Class E
PPE-HD-102	Vented Cap-Style Safety Helmet Lightweight ABS helmet with sliding vents and 6-point suspension for hot environments.	EN 397 (-30 °C, LD, MM)
PPE-HD-103	Electrical-Insulating Safety Helmet Non-vented HDPE helmet rated for live-working electrical environments, with chin strap.	EN 50365 Class 0; EN 397 440 V AC
PPE-HD-104	Bump Cap Baseball-style bump cap with ABS insert for low-clearance areas where hard hats are not required.	EN 812
PPE-HD-105	Height & Rescue Helmet Climbing-style helmet with EPS liner and 4-point chin strap for work at height and rescue teams.	EN 12492; EN 397
PPE-HD-106	Cap-Style Safety Helmet, Ratchet, ANSI Type I Front-peak HDPE helmet with 4-point suspension for general construction and plant work.	EN 397; ANSI/ISEA Z89.1 Type I Class E
PPE-HD-107	Type II Safety Helmet with Integrated Visor Lateral-impact helmet with EPS liner, retractable eye shield and chin strap for mixed-hazard sites.	ANSI/ISEA Z89.1 Type II Class E; EN 397; EN 166
PPE-HD-108	Helmet Accessory Kit: Chin Strap, Sweatband & Neck Shade Replacement and comfort accessories for slotted safety helmets used in hot climates.	Accessories for EN 397 helmets

EYE & FACE PROTECTION

SKU	Product	Standards
PPE-EY-201	Wraparound Safety Spectacles, Clear Polycarbonate wraparound spectacles with anti-scratch and anti-fog coating.	EN 166 1 F; EN 170; ANSI Z87.1+
PPE-EY-202	Safety Spectacles, Smoke Lens Outdoor safety spectacles with sun-glare filter for	EN 166; EN 172

SKU	Product	Standards
	bright desert conditions.	
PPE-EY-203	Indirect-Vent Chemical Splash Goggles Sealed goggles for liquid splash and dust; fit over prescription glasses.	EN 166 3 4 B; ANSI Z87.1 D3
PPE-EY-204	Face Shield with Brow Guard 200 mm polycarbonate visor on ratchet headgear for grinding and splash tasks.	EN 166 B; ANSI Z87.1
PPE-EY-205	Auto-Darkening Welding Helmet Variable shade 9–13 welding helmet with fast switching and solar-assisted power.	EN 379; EN 175
PPE-EY-206	Over-Spectacles for Prescription Wearers Polycarbonate over-glasses that fit over most prescription frames, with side shields and adjustable arms.	EN 166 1 F; ANSI Z87.1
PPE-EY-207	Passive Welding Goggles, Shade 5 Flip-Up Gas welding and cutting goggles with flip-up shade 5 filters over clear impact lenses.	EN 166; EN 169; EN 175
PPE-EY-208	Wall-Mounted Lens Cleaning Station Dispenser station with anti-fog cleaning fluid and silicone-free tissues for site eyewear.	—

HEARING PROTECTION

SKU	Product	Standards
PPE-HR-301	Disposable Foam Earplugs (200 pairs) Tapered PU foam earplugs for all-day comfort in high-noise areas.	EN 352-2
PPE-HR-302	Corded Reusable Earplugs Washable triple-flange earplugs with cord for intermittent noise exposure.	EN 352-2
PPE-HR-303	Over-Head Earmuffs Padded-headband earmuffs with low-pressure cushions for long shifts.	EN 352-1
PPE-HR-304	Helmet-Mounted Earmuffs Earmuffs that clip into standard 30 mm helmet slots.	EN 352-3
PPE-HR-305	Banded Earplugs, Under-Chin Lightweight band with replaceable foam pods for workers moving in and out of noise areas.	EN 352-2
PPE-HR-306	Electronic Level-Dependent Earmuffs Earmuffs with ambient microphones that amplify speech and limit impulse noise for situational awareness.	EN 352-1; EN 352-4; EN 352-6
PPE-HR-307	Earplug Dispenser with 500 Pairs Wall-mounted gravity dispenser preloaded with uncorded foam earplugs for site entrances.	EN 352-2 (earplugs)

RESPIRATORY PROTECTION

SKU	Product	Standards
PPE-RS-401	FFP2 Folding Respirator with Valve Fold-flat FFP2 respirator with exhalation valve for dust and mist.	EN 149:2001+A1:2009 FFP2 NR D
PPE-RS-402	FFP3 Moulded Respirator with Valve Moulded FFP3 respirator for fine particulates, dolomite tested for clog resistance.	EN 149 FFP3 R D
PPE-RS-403	Reusable Half-Mask Respirator Silicone half mask with bayonet twin-filter connection in three sizes.	EN 140
PPE-RS-404	Full-Face Respirator Wide-view full-face mask with standard Rd40 thread for gas and particle filters.	EN 136 Class 3
PPE-RS-405	Combination Filter A2B2E2K2-P3 Multi-gas and particulate filter for organic, inorganic, acid gases and ammonia.	EN 14387; EN 143
PPE-RS-406	Positive-Pressure SCBA, 6.8 L Composite Self-contained breathing apparatus with 300 bar composite cylinder and full-face mask for emergency response and entry work.	EN 137 Type 2
PPE-RS-407	Emergency Escape Breathing Device (EEBD) 15-minute constant-flow escape hood for evacuation from toxic or oxygen-deficient atmospheres.	ISO 23269-1; EN 1146
PPE-RS-408	H2S Escape Set, 10 Minute Compact hood-type escape set for sour gas facilities.	EN 1146
PPE-RS-409	Powered Air-Purifying Respirator (PAPR) with Hood Belt-mounted blower unit with loose-fitting hood for long-duration particulate and gas protection without a tight face seal.	EN 12941 TH3
PPE-RS-410	Constant-Flow Airline Respirator Set Compressed-air line breathing set with full-face mask and belt flow regulator for blasting, painting and tank work.	EN 14594 Class 3A; EN 12021 (air quality)

HAND PROTECTION

SKU	Product	Standards
PPE-HN-501	Nitrile-Coated General Handling Glove Breathable 15-gauge nylon glove with foam nitrile palm for dry and oily handling.	EN 388 4121X; EN 420
PPE-HN-502	Cut-Resistant Glove, Level C HPPE/glass-fibre liner with PU palm for sheet metal and glass handling.	EN 388 4X42C; ANSI/ISEA 105 A3
PPE-HN-503	Impact-Resistant Oil & Gas Glove Hi-vis glove with TPR back-of-hand protection and sandy nitrile grip for drilling and rigging.	EN 388 4X43E P; ANSI/ISEA 138 Level 2
PPE-HN-504	Chemical-Resistant Nitrile Gauntlet 33 cm flock-lined nitrile gauntlet for chemical handling.	EN ISO 374-1 Type A (JKLOPT); EN ISO 374-5
PPE-HN-505	Leather Welding Gauntlet Split cowhide gauntlet with aramid stitching for	EN 12477 Type A; EN 407

SKU	Product	Standards
	welding and hot work.	
PPE-HN-506	Electrical Insulating Glove, Class 0 Natural rubber insulating glove for live work up to 1000 V AC.	EN 60903 / IEC 60903 Class 0; ASTM D120
PPE-HN-507	Disposable Nitrile Gloves (100) Powder-free 4 mil nitrile gloves for light chemical and hygiene tasks.	EN ISO 374-1 Type B; EN 455
PPE-HN-508	Cut-Resistant Glove, Level F, HPPE 13-gauge HPPE/steel-fibre liner with sandy nitrile palm for sharp-edge handling of metal and glass.	EN 388 4X44F; ANSI/ISEA 105 A6
PPE-HN-509	Leather Rigger Glove Cowhide rigger glove with reinforced palm and cotton back for rigging and material handling.	EN 388 2122X; EN ISO 21420
PPE-HN-510	Heat-Resistant Aramid Glove, 250 °C Knitted aramid glove with terry lining for contact heat up to 250 °C in foundries and hot processes.	EN 407 X2XXXX; EN 388

FOOT PROTECTION

SKU	Product	Standards
PPE-FT-601	Leather Safety Boot S3 Full-grain leather boot with composite toecap, non-metallic midsole and heat-resistant outsole.	EN ISO 20345:2022 S3 SRC HRO
PPE-FT-602	Rigger Boot Pull-on rigger boot with steel toecap and heat-resistant nitrile sole.	EN ISO 20345 S3 HRO
PPE-FT-603	PVC Safety Wellington Oil and chemical resistant wellington with steel toe and midsole.	EN ISO 20345 S5
PPE-FT-604	Electrical Hazard Safety Shoe Metal-free shoe with composite toe for electrical hazard environments.	ASTM F2413 EH; EN ISO 20345 SB
PPE-FT-605	Safety Trainer Shoe S1P Lightweight sports-style safety shoe with composite toecap and textile puncture-resistant midsole for logistics and light industry.	EN ISO 20345 S1P SRC
PPE-FT-606	Chemical-Resistant PU Safety Boot S5 Lightweight polyurethane boot with insulating sole for chemical plants, utilities and wet areas.	EN ISO 20345 S5 CI SRC; EN 13832-3
PPE-FT-607	Leather Safety Boot S3, Zip-Side, Waterproof Lace-up boot with side zip and waterproof membrane for quick fitting on offshore and plant sites.	EN ISO 20345 S3 WR SRC HRO
PPE-FT-608	Steel Toe Overshoe for Visitors Slip-on rubber overshoe with steel toe guard for visitors and short site tours.	—

PROTECTIVE CLOTHING

SKU	Product	Standards
PPE-CL-701	Flame-Retardant Coverall 88/12 FR cotton/nylon coverall with reflective tape for oil, gas and petrochemical sites.	EN ISO 11612 A1 B1 C1 E1; EN ISO 11611 Class 1; IEC 61482-2
PPE-CL-702	Arc-Flash Coverall, 12 cal/cm² Inherently FR coverall for electrical arc-flash hazards.	IEC 61482-2; NFPA 70E Arc Rating 2
PPE-CL-703	Cotton Work Coverall, Desert Weight Breathable 100% cotton coverall with vents for hot climates.	EN ISO 13688
PPE-CL-704	Disposable Coverall Type 5/6 Hooded microporous coverall for dust and light liquid splash.	EN ISO 13982-1 Type 5; EN 13034 Type 6
PPE-CL-705	Chemical Splash Suit Type 3 PVC-coated suit with taped seams and attached hood for liquid chemical jets.	EN 14605 Type 3
PPE-CL-707	Aluminised Proximity Suit Aluminised para-aramid suit for short exposure to high radiant heat.	EN ISO 11612; EN 1486
PPE-CL-708	Leather Welding Jacket Split-leather welding jacket with stand-up collar and snap closures for heavy spatter work.	EN ISO 11611 Class 2 A1
PPE-CL-709	PVC Rain Suit, Jacket & Trousers Two-piece PVC-on-polyester rain suit with hood and welded seams.	EN 343 Class 3/1

HIGH-VISIBILITY CLOTHING

SKU	Product	Standards
PPE-CL-706	Hi-Vis Safety Vest, Class 2 Polyester mesh vest with two 50 mm reflective bands.	EN ISO 20471 Class 2; ANSI/ISEA 107 Type R Class 2
PPE-HV-711	Hi-Vis Jacket, Class 3 Waterproof hi-vis jacket for road and night work.	EN ISO 20471 Class 3
PPE-HV-712	Hi-Vis FR Shirt Flame-retardant hi-vis shirt combining visibility and heat protection.	EN ISO 20471 Class 2; EN ISO 11612
PPE-HV-713	Hi-Vis Trousers, Class 1 Polycotton work trousers with two reflective bands per leg and knee-pad pockets.	EN ISO 20471 Class 1
PPE-HV-714	Hi-Vis Polo Shirt, Short Sleeve Moisture-wicking bird-eye polyester polo with reflective bands for hot outdoor work.	EN ISO 20471 Class 2
PPE-HV-715	Hi-Vis Surveyor Vest with Pockets Zip-front surveyor vest with ID pocket, pen slots and tablet pocket for supervisors and engineers.	EN ISO 20471 Class 2; ANSI/ISEA 107 Type R Class 2
PPE-HV-716	Hi-Vis Waterproof Parka, Class 3 Insulated waterproof parka with taped seams and detachable hood for cold or wet night work.	EN ISO 20471 Class 3; EN 343

FALL PROTECTION

SKU	Product	Standards
PPE-FP-801	Full-Body Harness, 2-Point Dorsal and sternal attachment harness with quick-connect buckles.	EN 361; ANSI Z359.11
PPE-FP-802	Double-Leg Energy-Absorbing Lanyard 1.8 m webbing lanyard with scaffold hooks for 100% tie-off.	EN 355; EN 362
PPE-FP-803	Self-Retracting Lifeline, 6 m Webbing SRL with swivel top for vertical work.	EN 360; ANSI Z359.14 Class 1
PPE-FP-804	Confined-Space Tripod with Rescue Winch Aluminium tripod and winch for entry and retrieval at manholes and vessels.	EN 795 Type B; EN 1496
PPE-FP-805	Webbing Anchor Sling 1.0 m anchor sling for beams and structural members.	EN 795 Type B
PPE-FP-806	Full-Body Harness, 5-Point with Work Positioning Belt Harness with dorsal, sternal and side D-rings plus padded waist belt for tower and pole work.	EN 361; EN 358; ANSI Z359.11
PPE-FP-807	Rope Grab Fall Arrester with 20 m Kernmantle Line Guided-type fall arrestor running on a 12 mm kernmantle anchor line for vertical access.	EN 353-2
PPE-FP-808	Temporary Horizontal Lifeline, 20 m Portable webbing horizontal lifeline with tensioner and energy absorber for up to two users.	EN 795 Type C
PPE-FP-809	Twin Self-Retracting Lifeline, 2 m Compact twin-leg SRL connected at the dorsal D-ring for 100% tie-off when moving on structures.	EN 360; ANSI Z359.14 Class 1
PPE-FP-810	Tool Tether with Wrist Lanyard, 2.3 kg Shock-absorbing coiled tether and wrist strap to prevent dropped tools at height.	ANSI/ISEA 121

SECTION

Fire Fighting & Fire Protection

Portable extinguishers, hose reels, detection and alarm, suppression components and firefighter PPE.

FIRE EXTINGUISHERS

SKU	Product	Standards
FF-EX-101	ABC Dry Powder Extinguisher, 6 kg Stored-pressure multipurpose extinguisher for Class A, B and C fires.	EN 3-7; EN 3-8
FF-EX-103	CO2 Extinguisher, 5 kg Clean CO2 extinguisher for electrical equipment and flammable liquids.	EN 3-7
FF-EX-104	AFFF Foam Extinguisher, 9 L Foam extinguisher for Class A and B fires.	EN 3-7
FF-EX-105	Wet Chemical Extinguisher, 6 L For commercial kitchen cooking oil and fat fires (Class F).	EN 3-7
FF-EX-106	Wheeled Dry Powder Extinguisher, 50 kg Trolley extinguisher for fuel depots, workshops and plant areas.	EN 1866-1
FF-EX-107	ABC Dry Powder Extinguisher, Stored Pressure Range Portable multipurpose extinguishers in common sizes for vehicles, offices and plant areas.	EN 3-7
FF-EX-108	Water Mist Extinguisher, 6 L Deionised water mist extinguisher for Class A, F and tested electrical risks with minimal residue.	EN 3-7
FF-EX-109	CO2 Extinguisher, 2 kg Compact CO2 unit for server rooms, switchboards and electrical panels.	EN 3-7
FF-EX-110	Automatic Ceiling-Mounted Powder Extinguisher, 6 kg Modular extinguisher that discharges automatically when its glass bulb bursts, for generator, pump and store rooms.	Manufacturer test data; EN 3-7 agent
FF-EX-111	Wheeled Foam Extinguisher, 50 L AFFF trolley extinguisher with hose and foam branch for fuel storage and loading areas.	EN 1866-1

HOSE REELS, HOSES & CABINETS

SKU	Product	Standards
FF-HC-203	Double Fire Hose Cabinet Surface-mounted steel cabinet housing hose reel and extinguishers.	EN 671-1 (when fitted with reel)
FF-HC-206	Single Fire Hose Reel Cabinet, Recessed Recessed steel cabinet for a single hose reel with space for one extinguisher.	EN 671-1 (when fitted with reel)
FF-HR-201	Swinging Hose Reel, 30 m × 25 mm Semi-rigid hose reel with jet/spray nozzle and isolation valve.	EN 671-1
FF-HR-204	Fixed Hose Reel with Auto Valve, 30 m × 19 mm Fixed wall reel with automatic inlet valve that opens as the hose is drawn out.	EN 671-1
FF-HS-202	Lay-Flat Fire Hose, 2.5" × 30 m Rubber-lined synthetic hose with instantaneous couplings.	EN 14540
FF-HS-205	Lay-Flat Fire Hose, 1.5 in × 30 m Lightweight rubber-lined hose with instantaneous couplings for internal hydrant and landing valve use.	EN 14540
FF-LV-207	Oblique Landing Valve, 2.5 in Gunmetal landing valve with instantaneous outlet and blank cap for wet and dry risers.	BS 5041-1
FF-NZ-208	Dual-Purpose Branch Pipe Nozzle Jet/spray branch with shut-off for 1.5 in and 2.5 in lay-flat hoses.	EN 15182

FIRE DETECTION & ALARM

SKU	Product	Standards
FF-FA-501	Addressable Fire Alarm Panel, 2 Loop Networkable addressable panel with touchscreen for medium to large sites.	EN 54-2; EN 54-4
FF-FA-502	Addressable Optical Smoke Detector Photoelectric smoke detector with 360° LED and isolator base.	EN 54-7
FF-FA-503	IR3 Flame Detector, Explosion-Proof Triple-IR flame detector for hydrocarbon fires in hazardous areas.	EN 54-10; ATEX/IECEx
FF-FA-504	Heat Detector, Fixed / Rate-of-Rise Heat detector for kitchens, garages and dusty areas.	EN 54-5
FF-FA-505	Manual Call Point Resettable red call point for alarm activation.	EN 54-11
FF-FA-506	Conventional Fire Alarm Panel, 4 Zone Compact conventional control panel for small buildings, warehouses and site offices.	EN 54-2; EN 54-4
FF-FA-507	Multi-Sensor Optical/Heat Detector Combined smoke and heat detector that reduces false alarms in areas with steam or dust.	EN 54-7; EN 54-5
FF-FA-508	Reflective Optical Beam Smoke Detector Single-ended beam detector for warehouses,	EN 54-12

SKU	Product	Standards
	hangars and atriums with high ceilings.	
FF-FA-509	Wall Sounder Beacon, Red Combined sounder and visual alarm device for alerting occupants in noisy or hearing-impaired areas.	EN 54-3; EN 54-23
FF-FA-510	Linear Heat Detection Cable, 68 °C Digital heat-sensing cable for conveyors, cable trays and tank roofs.	EN 54-28

FIRE SUPPRESSION

SKU	Product	Standards
FF-FM-301	AR-AFFF 3x3 Foam Concentrate, 200 L Alcohol-resistant foam concentrate for hydrocarbon and polar solvent fires.	EN 1568-3; EN 1568-4
FF-FM-302	AFFF 3% Foam Concentrate, 20 L Film-forming foam concentrate for hydrocarbon fuel fires through inductors and foam branches.	EN 1568-3
FF-FM-303	Fluorine-Free Foam Concentrate 3%, 200 L PFAS-free synthetic foam concentrate for hydrocarbon fire response and training.	EN 1568-3
FF-SP-401	Pendent Sprinkler Head, 68 °C Standard-response pendent sprinkler with glass bulb.	EN 12259-1
FF-SP-402	Upright Sprinkler Head, 68 °C Standard-response upright sprinkler for exposed pipework in plant rooms and warehouses.	EN 12259-1
FF-SP-403	Sidewall Sprinkler Head, Quick Response Horizontal sidewall sprinkler for corridors and rooms where ceiling pipework is impractical.	EN 12259-1
FF-SP-404	Clean Agent Suppression System, FK-5-1-12 Engineered total-flooding system for server rooms, control rooms and archives, designed per room volume.	ISO 14520; NFPA 2001
FF-SP-405	Kitchen Hood Wet Chemical Suppression System Pre-engineered wet chemical system for commercial kitchen hoods, ducts and fryers with automatic gas shut-off.	UL 300; NFPA 17A
FF-SP-406	Condensed Aerosol Suppression Unit Compact aerosol generator for electrical cabinets, enclosures and small machinery spaces.	ISO 15779

FIREFIGHTER PPE

SKU	Product	Standards
FF-PP-701	Structural Firefighting Suit Three-layer suit with moisture barrier and reflective trim.	EN 469 Level 2
FF-PP-702	Firefighter Helmet Composite firefighter helmet with integrated	EN 443

SKU	Product	Standards
	visor.	
FF-PP-703	Firefighting Gloves Aramid/leather gloves with waterproof membrane.	EN 659
FF-PP-704	Firefighter Boots Leather firefighter boots with steel toe and heat-resistant sole.	EN 15090 F2A HI3 CI SRC
FF-PP-705	Firefighter Flash Hood Double-layer knitted hood that protects the head and neck around SCBA masks.	EN 13911
FF-PP-706	Firefighting Thermal Imaging Camera Handheld thermal camera for search and rescue, hotspot location and overhaul in smoke.	NFPA 1801 (type)
FF-PP-707	Personal Alert Safety System (PASS) Device Motion-sensing alarm that sounds if a firefighter remains motionless, with manual distress button.	EN 16473 (type); NFPA 1982
FF-PP-708	Wildland Firefighting Coverall Lightweight single-layer FR coverall for vegetation and wildland fire response.	EN ISO 15384

EMERGENCY LIGHTING & SIGNAGE

SKU	Product	Standards
FF-EL-801	LED Emergency Exit Sign, Maintained Self-testing maintained exit sign with 3-hour battery and bilingual legend.	EN 1838; EN 60598-2-22; ISO 7010
FF-EL-803	LED Emergency Bulkhead Luminaire, Non-Maintained IP65 bulkhead for escape routes and plant areas that lights on mains failure.	EN 60598-2-22; EN 1838
FF-EL-804	Twin-Spot Emergency Light Wall-mounted twin LED spot unit for warehouses, stairwells and car parks.	EN 60598-2-22
FF-FB-601	Fire Blanket 1.2 × 1.8 m Woven glass-fibre fire blanket with quick-release tabs.	EN 1869
FF-FB-602	Fire Blanket 1.0 × 1.0 m, Kitchen Compact glass-fibre fire blanket in a quick-release pouch for kitchens and pantries.	EN 1869
FF-SG-802	Photoluminescent Fire Equipment Sign Set Glow-in-the-dark signs for extinguishers, hose reels and call points.	ISO 7010
FF-SG-805	Photoluminescent Exit Sign, Bilingual Glow-in-the-dark exit direction sign with Arabic and English legend.	ISO 7010 E001/E002; ISO 16069
FF-SG-806	Photoluminescent Low-Location Floor Marking Tape Self-adhesive glow tape for marking escape routes, steps and doorways at low level.	ISO 16069

SECTION

Gas Detection & Environmental

Portable and fixed gas detection, calibration equipment and occupational hygiene monitoring.

PORTABLE GAS DETECTORS

SKU	Product	Standards
GD-PT-101	Single-Gas H2S Detector, 2-Year Maintenance-free personal H2S monitor with vibrating, audible and visual alarms.	ATEX II 1G Ex ia IIC T4; IECEx
GD-PT-102	4-Gas Portable Detector LEL, O2, CO and H2S monitor for confined-space entry and hot work.	ATEX/IECEx Zone 0; EN 60079-29-1; EN 50104
GD-PT-103	Multi-Gas Detector with PID Six-sensor pumped detector including PID for VOCs.	ATEX/IECEx; EN 45544
GD-PT-104	Transportable Area Monitor Wireless area monitor for perimeter and shutdown monitoring.	ATEX Zone 1
GD-PT-105	Single-Gas CO Detector, 2-Year Disposable personal carbon monoxide monitor for workshops, boiler rooms and vehicle bays.	ATEX/IECEx Zone 0; EN 45544
GD-PT-106	Single-Gas O2 Detector, Replaceable Sensor Personal oxygen monitor for confined spaces and inert-gas areas with replaceable sensor and battery.	ATEX/IECEx; EN 50104
GD-PT-107	Single-Gas SO2 Detector Personal sulphur dioxide monitor for refineries, sulphur recovery units and smelters.	ATEX/IECEx; EN 45544
GD-PT-108	5-Gas Detector with IR CO2 Sensor Pumped or diffusion multi-gas monitor adding infrared CO2 to LEL, O2, CO and H2S.	ATEX/IECEx; EN 60079-29-1; EN 50104
GD-PT-109	Motorised Sampling Pump Module Clip-on pump with probe and tubing for remote sampling before confined-space entry.	ATEX/IECEx
GD-PT-110	Colorimetric Gas Detector Tubes with Hand Pump Bellows hand pump and short-term detector tubes for spot measurement of specific gases and vapours.	EN ISO 17621

FIXED GAS DETECTION

SKU	Product	Standards
GD-FX-201	Fixed IR Hydrocarbon Gas Detector Infrared point detector with HART and Modbus outputs in stainless housing.	ATEX/IECEX Ex d; IEC 61508 SIL 2; EN 60079-29-1
GD-FX-202	Fixed H2S Transmitter Electrochemical H2S transmitter with local display and non-intrusive calibration.	ATEX/IECEX; IEC 61508 SIL 2
GD-FX-204	Gas Detection Control Panel, 8 Channel Controller for fixed detectors with relay outputs and event log.	EN 50271
GD-FX-205	Catalytic Combustible Gas Detector Catalytic bead point detector for flammable gases in plant rooms and process areas.	ATEX/IECEX; EN 60079-29-1
GD-FX-206	Open-Path IR Gas Detector Line-of-sight infrared transmitter/receiver pair for hydrocarbon gas clouds across process areas and fence lines.	ATEX/IECEX; EN 60079-29-4; IEC 61508 SIL 2
GD-FX-207	Ultrasonic Gas Leak Detector Acoustic detector that senses airborne ultrasound from pressurised gas leaks regardless of wind direction.	ATEX/IECEX; IEC 61508 SIL 2
GD-FX-208	Toxic Gas Transmitter, Electrochemical (CO, NH3, Cl2) Configurable electrochemical transmitter with plug-in sensor for common toxic gases.	ATEX/IECEX; EN 45544
GD-FX-209	Wireless Gas Detector, Battery Powered Battery-powered point detector on a wireless network for temporary or hard-to-wire locations.	ATEX/IECEX
GD-FX-210	Weather Protection & Calibration Cap Kit Sensor accessories for fixed detectors: weather guard, calibration adapter and collecting cone.	—

CALIBRATION & DOCKING

SKU	Product	Standards
GD-CL-301	4-Gas Calibration Cylinder, 58 L Certified mixture for bump testing and calibration of 4-gas detectors.	ISO 6141
GD-CL-302	Automatic Bump-Test Station Docking station for bump tests, calibration and record keeping.	Manufacturer-specific
GD-CL-303	Fixed-Flow Regulator, 0.5 L/min Brass regulator with gauge for calibration cylinders used with diffusion detectors.	—
GD-CL-304	Demand-Flow Regulator Regulator that supplies gas only when drawn by a pumped instrument, conserving calibration gas.	—
GD-CL-305	Single-Gas Calibration Cylinder, H2S 25 ppm Certified H2S in nitrogen mixture for single-gas H2S monitors.	ISO 6141 (certificate)
GD-CL-306	Zero Air Calibration Cylinder, 58 L Synthetic air for zeroing sensors where the ambient atmosphere may be contaminated.	ISO 6141 (certificate)

SKU	Product	Standards
GD-CL-307	Portable Calibration Kit in Carry Case Field kit with regulator, tubing and calibration adapters for site calibration of portable detectors.	—

ENVIRONMENTAL MONITORING

SKU	Product	Standards
EN-AQ-401	Indoor Air Quality Monitor Monitors CO2, particulates, TVOC, temperature and humidity.	—
EN-DS-404	Handheld Particulate Monitor, PM1/PM2.5/PM10 Laser-scattering dust monitor for site dust surveys and indoor air checks.	—
EN-HS-403	WBGT Heat Stress Monitor Heat stress monitor with work-rest alarms for hot-climate operations.	ISO 7243
EN-NS-402	Sound Level Meter / Noise Dosimeter Class 2 meter for noise surveys and personal exposure.	IEC 61672-1 Class 2; IEC 61252
EN-NS-406	Personal Noise Dosimeter, Shoulder-Worn Cable-free shoulder dosimeter for full-shift personal noise exposure measurement.	IEC 61252; IEC 61672-1 Class 2
EN-RD-408	Personal Radiation Dosimeter Electronic gamma/X-ray dosimeter for radiography crews and NORM handling.	IEC 61526
EN-SP-405	Personal Air Sampling Pump Belt-worn constant-flow pump for workplace exposure sampling with filters and sorbent tubes.	EN ISO 13137
EN-TH-407	Thermo-Hygrometer & Anemometer Handheld instrument for air temperature, humidity and air velocity in ventilation and comfort surveys.	—

SECTION

Emergency & Rescue

Emergency showers and eyewash, first aid and AEDs, stretchers and confined-space rescue.

EYEWASH & SAFETY SHOWERS

SKU	Product	Standards
ER-EW-101	Combination Emergency Shower & Eyewash Plumbed galvanised shower and eyewash with stay-open valves.	ANSI/ISEA Z358.1; EN 15154-1/-2
ER-EW-102	Self-Contained Portable Eyewash, 60 L Gravity-fed eyewash providing a 15-minute flush for remote locations.	ANSI/ISEA Z358.1
ER-EW-103	Pedestal Eye/Face Wash Station Floor-mounted plumbed eye/face wash with stainless bowl and push-flag valve.	ANSI/ISEA Z358.1; EN 15154-2
ER-EW-104	Wall-Mounted Eyewash Station Compact wall eyewash for laboratories and workshops connected to potable water.	ANSI/ISEA Z358.1; EN 15154-2
ER-EW-105	Tank Safety Shower with Eyewash, 1,000 L Self-contained tank shower for remote sites with no plumbed supply, with insulated tank for desert climates.	ANSI/ISEA Z358.1; EN 15154-4
ER-EW-106	Personal Eyewash Bottle Station Wall station with two sterile saline bottles for immediate eye flushing before reaching a plumbed unit.	Supplementary to ANSI/ISEA Z358.1
ER-EW-107	Drench Hose, Bench-Mounted Dual-head hand-held drench hose for laboratories and benches.	EN 15154-2 (type); ANSI/ISEA Z358.1 supplementary

FIRST AID & AED

SKU	Product	Standards
ER-FA-201	Industrial First Aid Kit, 50 Person Wall-mounted first aid kit with bilingual contents list.	BS 8599-1
ER-FA-202	Automated External Defibrillator (AED) Semi-automatic AED with voice prompts in Arabic and English.	IEC 60601-2-4
ER-FA-203	Vehicle First Aid Kit Compact soft-case kit for company vehicles and service vans.	BS 8599-2

SKU	Product	Standards
ER-FA-204	Bleeding Control Trauma Kit Haemorrhage control kit with windlass tourniquet, haemostatic gauze and pressure bandage for serious injuries.	—
ER-FA-205	Burns Kit with Hydrogel Dressings Burns kit for kitchens, welding bays and hot-work areas.	—
ER-FA-206	Oxygen Resuscitation Kit Portable oxygen kit with regulator, masks and bag-valve-mask for trained first responders.	—
ER-FA-207	AED Wall Cabinet with Alarm Indoor wall cabinet for an AED with door-open alarm and signage.	ISO 7010 E010 (sign)
ER-FA-208	First Aid Kit Refill Pack, 50 Person Replenishment pack for workplace first aid kits after use or expiry.	BS 8599-1

RESCUE & EVACUATION

SKU	Product	Standards
ER-RS-306	Explosion-Proof Ventilation Blower with Ducting Axial blower with flexible duct for purging and ventilating confined spaces before and during entry.	ATEX/IECEX
ER-RS-307	Manhole Guard Rail Folding steel guard that surrounds open manholes during entry and rescue operations.	—
ER-RS-308	Pre-Rigged Rescue & Lowering Kit Ready-to-use pulley system for raising or lowering a casualty from height or confined space.	EN 1496; EN 341
ER-ST-301	HDPE Basket Stretcher Rescue basket for rope and helicopter recovery.	EN 1865
ER-ST-302	Evacuation Chair Stair-descent evacuation chair for mobility-impaired occupants.	—
ER-ST-303	Spine Board with Head Immobiliser X-ray translucent polyethylene spine board with straps and head blocks.	EN 1865-1
ER-ST-304	Aluminium Scoop Stretcher Split-frame stretcher that separates lengthways to lift casualties with minimal movement.	EN 1865-1
ER-ST-305	Roll-Up Rescue Sled Stretcher Flexible polymer stretcher that rolls for storage and wraps the casualty for confined-space and vertical extraction.	EN 1865-1

SECTION

Site Safety & Industrial Supplies

Lockout/tagout, spill control, traffic management, signage and hazardous-material storage.

LOCKOUT / TAGOUT

SKU	Product	Standards
SS-LT-401	Lockout Station, 10 Padlock Complete LOTO station with padlocks, hasps, tags and breaker locks.	Supports OSHA 29 CFR 1910.147 programmes
SS-LT-402	Safety Padlock, Keyed Different Non-conductive nylon-body padlock for energy isolation.	—
SS-LT-403	Steel Lockout Hasp, 6-Hole Scissor hasp allowing up to six workers to apply personal locks to one isolation point.	Supports OSHA 29 CFR 1910.147 programmes
SS-LT-404	Adjustable Ball Valve Lockout Polypropylene device that locks quarter-turn ball valves in the off position.	Supports OSHA 29 CFR 1910.147 programmes
SS-LT-405	Gate Valve Lockout Rotating cover that encloses gate valve handwheels to prevent operation.	Supports OSHA 29 CFR 1910.147 programmes
SS-LT-406	Miniature Circuit Breaker Lockout Set Set of clip-on lockouts for single-pole and multi-pole miniature circuit breakers.	Supports OSHA 29 CFR 1910.147 programmes
SS-LT-407	Group Lock Box, Wall-Mounted Steel box for group lockout where isolation keys are secured until every worker removes their lock.	Supports OSHA 29 CFR 1910.147 programmes
SS-LT-408	Danger Do Not Operate Tags, Bilingual (25) Tear-resistant lockout tags with Arabic and English legend and write-on area.	ANSI Z535.5 format
SS-LT-409	Personal Lockout Kit in Pouch Belt pouch kit with padlocks, hasp, breaker lockouts and tags for maintenance technicians.	Supports OSHA 29 CFR 1910.147 programmes

SPILL CONTROL

SKU	Product	Standards
SS-SP-501	Oil-Only Spill Kit, 240 L Wheeled spill kit for hydrocarbon spills.	—

SKU	Product	Standards
SS-SP-502	Universal Spill Kit, 120 L Absorbs oils, coolants and non-aggressive chemicals.	—
SS-SP-503	Chemical Spill Kit, 120 L Kit with yellow chemical absorbents for acids, alkalis and aggressive liquids.	—
SS-SP-504	Oil-Only Absorbent Pads (100) Hydrophobic polypropylene pads that absorb oil and repel water for workshops and marine use.	—
SS-SP-505	Universal Absorbent Socks, 1.2 m (20) Grey general-purpose socks for containing leaks around machinery and drums.	—
SS-SP-506	Polyurethane Drain Cover, 600 × 600 mm Reusable drain seal that prevents spills from entering storm drains.	—
SS-SP-507	4-Drum Spill Pallet Polyethylene sump pallet that stores four 205 L drums with removable grid.	Bund sized per typical 110%/25% rules
SS-SP-508	Vehicle Spill Kit, 50 L Compact holdall kit for tankers, service trucks and mobile plant.	—

TRAFFIC & BARRIERS

SKU	Product	Standards
SS-TB-601	Traffic Cone, 750 mm Reflective PVC cone with reflective collars for road works and site traffic.	EN 13422
SS-TB-602	Water-Filled Barrier, 2 m Interlocking water-filled barrier for traffic separation.	—
SS-TB-603	Flexible PVC Traffic Cone Range Orange PVC cones with reflective sleeves in common heights for car parks, roads and plant areas.	EN 13422
SS-TB-604	Plastic Chain & Post Barrier Kit Red/white posts with plastic chain for quick pedestrian segregation around work areas.	—
SS-TB-605	Retractable Belt Barrier, 9 m Wall-mounted retractable belt for temporarily closing off aisles, doorways and work zones.	—
SS-TB-606	Rubber Speed Bump Section, 500 mm Bolt-down recycled-rubber speed hump modules with reflective inserts.	—
SS-TB-607	Convex Traffic Mirror, 800 mm Outdoor polycarbonate convex mirror for blind corners and site exits.	—

SAFETY SIGNS

SKU	Product	Standards
SS-SG-701	ISO 7010 Mandatory PPE Sign Bilingual mandatory sign for helmet, glasses and boots.	ISO 7010
SS-SG-702	ISO 7010 Prohibition Sign, No Smoking / No Naked Flames Bilingual prohibition sign for fuel areas, stores and hazardous zones.	ISO 7010 P002 / P003
SS-SG-703	ISO 7010 Warning Sign, Electrical Hazard Bilingual warning sign for switchrooms, panels and substations.	ISO 7010 W012
SS-SG-704	ISO 7010 Safe Condition Sign, Assembly Point Reflective post-mounted muster point sign for evacuation planning.	ISO 7010 E007
SS-SG-705	Pipe Marker Set to ASME A13.1 Colour-coded self-adhesive pipe markers with flow arrows for common plant fluids.	ASME A13.1; BS 1710 (alternative)
SS-SG-706	GHS Chemical Hazard Labels (250) Roll of GHS pictogram labels for secondary containers and decanted chemicals.	UN GHS; ISO 7010 (pictogram style)

HAZMAT STORAGE

SKU	Product	Standards
SS-ST-601	Flammable Storage Cabinet, 45 gal Double-wall steel cabinet with self-closing doors.	EN 14470-1 / NFPA 30
SS-ST-602	Corrosive Storage Cabinet, 30 gal Polyethylene-lined cabinet for acids and alkalis with leak-proof sump.	NFPA 30 (design reference)
SS-ST-603	Flammable Storage Cabinet, 12 gal Under-Bench Compact cabinet for small quantities of flammable liquids at the point of use.	NFPA 30; EN 14470-1 (fire-resistant versions)
SS-ST-604	Gas Cylinder Storage Cage, 10 Cylinders Outdoor mesh cage with lockable gate and chain restraints for compressed gas cylinders.	Design reference: BCGA CP44
SS-ST-605	Gas Cylinder Trolley, Twin Two-cylinder trolley for oxy-fuel sets with chain restraints and puncture-proof wheels.	—
SS-ST-606	Safety Can, Type I, 5 L Galvanised steel safety can with flame arrester and spring-closing lid for dispensing flammables.	Designed to OSHA 1910.106 / NFPA 30 safety can criteria
SS-ST-607	Outdoor Hazmat Storage Locker, 4-Drum Ventilated steel locker with integral sump for storing drums of flammable or hazardous liquids outdoors.	Design reference: NFPA 30